

Example 7.36 (Differential equation to system function). A LTI system with input x and output y is characterized by the differential equation

$$y''(t) + \frac{D}{M}y'(t) + \frac{K}{M}y(t) = x(t),$$

where D , K , and M are positive real constants, and the prime symbol is used to denote derivative. Find the system function H of this system.

Solution. Taking the Laplace transform of the given differential equation, we obtain

$$s^2Y(s) + \frac{D}{M}sY(s) + \frac{K}{M}Y(s) = X(s).$$

Rearranging the terms and factoring, we have

$$\left(s^2 + \frac{D}{M}s + \frac{K}{M}\right)Y(s) = X(s).$$

Dividing both sides by $\left(s^2 + \frac{D}{M}s + \frac{K}{M}\right)X(s)$, we obtain

$$\frac{Y(s)}{X(s)} = \frac{1}{s^2 + \frac{D}{M}s + \frac{K}{M}}.$$

Thus, H is given by

$$H(s) = \frac{1}{s^2 + \frac{D}{M}s + \frac{K}{M}}.$$

taking LT using
time-domain differentiation
property

rearrange terms and factor

divide both sides by
 $\left(s^2 + \frac{D}{M}s + \frac{K}{M}\right)X(s)$

$Y(s) = X(s)H(s) \Rightarrow$
 $H(s) = \frac{Y(s)}{X(s)}$

■