

Example 4.7. Consider the system with input x , output y , and impulse response h as shown in Figure 4.9. Each subsystem in the block diagram is LTI and labelled with its impulse response. Find h .

Solution. From the left half of the block diagram, we can write To begin, we label all signals in Figure 4.9.

$$\begin{aligned}
 \textcircled{1} \quad v(t) &= x(t) + x * h_1(t) + x * h_2(t) \\
 &= x * \delta(t) + x * h_1(t) + x * h_2(t) \\
 &= (x * [\delta + h_1 + h_2])(t).
 \end{aligned}$$

*δ is convolutional identity
distributive property*

Similarly, from the right half of the block diagram, we can write

$$y(t) = v * h_3(t). \quad \textcircled{2}$$

Substituting the expression for v into the preceding equation we obtain

$$\begin{aligned}
 y(t) &= v * h_3(t) \\
 &= (x * [\delta + h_1 + h_2]) * h_3(t) \\
 &= x * [h_3 + h_1 * h_3 + h_2 * h_3](t).
 \end{aligned}$$

*from ②
substituting ① for v
distributive and associative properties and convolutional identity*

Thus, the impulse response h of the overall system is

$$h(t) = h_3(t) + h_1 * h_3(t) + h_2 * h_3(t). \quad \blacksquare$$




Figure 4.9: System interconnection example.

Recall that, for any LTI system with input x , output y , and impulse response h , $y = x * h$.